


JN6516-S

2MP AHD & IP Hybrid DVR

- 16 CH analog video input, compatible with 5MP/4MP/1080p/720p AHD camera and CVBS input
- 8CH IPC input, compatible with 5MP/4MP/3MP/1080p/720p camera
- 2 SATA HDD, up to 8TB per HDD
- H.265/ H.264 compression
- Video management with sureSIGHT
- Supporting sureLINK for dynamic IP Internet connection
- iView HD for remote monitoring on mobile phones



Unit: mm



Model

JN6516-S

VIDEO INPUT	ANALOG CAMERA	compatible with 5MP / 4MP / 1080P / 720P AHD camera and CVBS input
	NO. OF CHANNEL	BNC x 16
VIDEO OUTPUT	IP CAMERA	Compatible with 5MP / 4MP / 3MP / 1080P / 720P IP camera
	NO. OF CHANNEL	8
AUDIO	DIGITAL VIDEO	1 channel 1920x1080 / 1280x1024 / 1024x768
	VGA	1 channel, 1920x1080 / 1280x1024 / 1024x768
	BNC	CVBS (used as the main or spot output)
RECORDING	INPUT	RCA x 8
	OUTPUT	RCA x 1
	IP CAMERA AUDIO INPUT	8
COMMUNICATION	COMPRESSION	H.265 / H.264
	MODE	Manual, Schedule, Motion, Event-driven
	HDD TYPE	SATA x2 (Max. 8TB per HDD)
	MAX. RECORDING PERFORMANCE	<p>Normal:</p> <p>1080P@12fps(PAL) / 15fps (NTSC) 720P@25fps (PAL) / 30fps (NTSC) CVBS WD1@25fps (PAL) / 30fps (NTSC)</p> <p>Lite mode:</p> <p>5MP Lite(1280x1936)@10fps, 4MP Lite(1280x1440)@12fps(PAL) / 15fps (NTSC), 1080P Lite(960x1080)@25fps (PAL) / 30fps (NTSC)</p>
EVENT HANDLING	PLAYBACK	16CH playback Play, Forward, Backward, Pause, Digital zoom, etc.
	NETWORK	RJ45 1000Mbps x 1
POWER	CONCURRENT USER	10
	WEB SERVER	Built-in
	RS485	RS485 x1, connect to PTZ or keyboard
	USB	USB2.0 x 2
OPERATING ENVIRONMENT	EVENT TYPE	Video motion detection, External alarm, Video loss
	ACTION TYPE	Recording, Snap, Email, Preset
	ALARM INPUT	16
	RELAY OUTPUT	4
MECHANICAL DESIGN	VOLTAGE	DC 12V
	POWER SUPPLY	DC12V / 4A
	MAX. RATING	≤ 15W(without HDD)
ENVIRONMENT	AMBIENT TEMPERATURE	-10°C - 50°C
	RELATIVE HUMIDITY	10% - 90%
MECHANICAL DESIGN	DIMENSION	380mm (W) x 280mm (D) x 52mm (H)
	WEIGHT	1.58kg

Terms & Conditions 使用細則

Design and specifications are subject to change without prior notice. Copyright © 2018 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners.